



TruTool TKF 1100

Technical data

**TruTool TKF 1100 30°
bevel angle****TruTool TKF 1100
37.5° bevel angle****TruTool TKF 1100 45°
bevel angle****MAXIMUM CHAMFER LENGTHS**

MAX. CHAMFER LENGTH, STEEL 400 N/MM ²	11 mm	11 mm	11 mm
MAX. CHAMFER LENGTH, STEEL 600 N/MM ²	9 mm	9 mm	9 mm
MAX. CHAMFER LENGTH, STEEL 800 N/MM ²	6 mm	6 mm	6 mm

RADII

SMALLEST RADIUS	40 mm	40 mm	40 mm
-----------------	-------	-------	-------

GENERAL

WORKING SPEED	2 m/min	2 m/min	2 m/min
STROKE RATE WITH NOMINAL LOAD	340 / 440 RPM	340 / 440 RPM	340 / 440 RPM
NOMINAL POWER CONSUMPTION	1600 W	1600 W	1600 W
SHEET THICKNESS	3 mm - 25 mm	3 mm - 25 mm	3 mm - 25 mm

WEIGHT

WEIGHT WITHOUT CABLE	10 kg	10 kg	10 kg
----------------------	-------	-------	-------

Subject to changes. The details in our offer and order confirmation are definitive.